133 Cecil Street # 12-03 Keck Seng Tower, Singapore 069535,

Republic Of Singapore

Tel. +65 6227 6365 - **Fax**. +65 6225 6286

www.chemtradeasia.com



Material Safety Data Sheet White Spirit

Section 1: Identification Of Substance / Preparation & Company

Product / Material : WHITE SPIRIT

Chemical Name and Synonyms: HYDROCARBON SOLVENT

Company Identification : Tradeasia International Pte Limited

Address : 133 Cecil Street # 12-03 Keck Seng Tower, Singapore

Tel:+65-6227 6365 Fax:+65-6225 6286

Email: contact@chemtradeasia.com

Section 2 : Composition / Information On Ingredients

Ingredient Name	CAS No	Contents	Health Risk
Petroleum distillate	64742–82 - 1	(Class) Xn	(R No.) 65
Primarily paraffinie			
Hydrocarbons			

Eu Index : No: 649-330-00-2

Formula : N/A

CAS No : 64742 – 82 – 1

Composition Comments: Benzene (CAS No. 71 - 43 - 2) will normally be present in Trace

amounts, but will always be less than 0.1% w/w marker level in the 21st ATP to the Dangerous Substance Directive. This White Spirit is not Classified as a carcinogen under 67/548/EEC and the CHIP regulations

1996.

133 Cecil Street # 12-03 Keck Seng Tower, Singapore 069535,

Republic Of Singapore

Tel. +65 6227 6365 - Fax. +65 6225 6286

www.chemtradeasia.com



Section 3 : Hazards Indentification

Flammable.

Harmful: May cause lung damage if swallowed. In the environment it is likely to biodegrade slowly. On the basis of information supplied it is unlikely to be hazardous to man in normal use; it should, however be noted that is classified as Flammable.

Section 4 : First Aid Measures

General: Do not give victim anything to drink if he/she is unconscious.

Inhalation:

If inhalation of fumes irritates the nose or throat or causes coughing remove to fresh air. Get medical advice if Irritation continues.

Ingestion:

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Get Medical attention. Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Do not induce vomiting because of the danger of aspiration. Ingestion of large quantities may cause nausea and diarrhoea.

Skin:

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Get medical attention promptly if symptoms occur after washing.

Eyes:

Promptly wash eyes with plenty of water while lifting the eyelids. Get medical attention if any discomfort continues. Continue to rinse for at least 15 minutes.

Section 5 : Fire Fighting Measures

Extinguishing Media: Carbon dioxide (CO2). Dry chemicals, sand, dolomite Etc. Foam.

Special Fire Fighting Procedures: Fires in closed or confined spaces should be tackled by trained personnel who should wear breathing apparatus.

Hazardous Decomposition Products: Carbon monoxide (CO). Oxides of: Carbon.

133 Cecil Street # 12-03 Keck Seng Tower, Singapore 069535,

Republic Of Singapore

Tel. +65 6227 6365 - Fax. +65 6225 6286

www.chemtradeasia.com



Section 6: Accidental Release Measures / Spills And Leaks

Spill Cleanup Method: Main consideration is to avoid fire. Classified Flammable. CONTAIN SPILLAGE. DO NOT WASH SPILLAGE DOWN THE DRAIN. Absorb in vermiculite, dry sand or Earth and place into containers. May cause slippery surfaces.

Section 7: Handling And Sotrage

Usage Precautions:

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Where prolonged or repeated exposure is likely PROTECTIVE CLOTHING should be worn including IMPERVIOUS GLOVES and EYE PROTECTION. Ensure good ventilation.

Storage Precautions:

Keep in cool, dry, ventilated storage and closed containers. Ground container and transfer equipment to eliminate static electric sparks. Protect from light, including direct sunrays. Flammable/ combustible – Keep away from oxidizers, heat and flames.

Storage Criteria: Flammable liquid storage.

Section 8 : Exposure Controls / Personal Protection

Ingredient Name	CAS No	STD	LT EXP	ST EXP
Petroleum distillate	64742-82-1	OEL	(8 hrs)	(15min)
primarily			600.00 mg/m3	
Paraffinic hydrocarbons		16/		1 1

Ingredient Comments: OEL calculated by using the Reciprocal Calculation Procedure (EH40 / 96)

Ventilation: LTEL has been established by using the Reciprocal Calculation procedure for mixed exposures to Hydrocarbon solvents in EH40.

Protective Gloves: Use suitable protective gloves if risk of skin contact.

Eye Protection: Wear splash – proof eye goggles to prevent any possibility of eye contact.

133 Cecil Street # 12-03 Keck Seng Tower, Singapore 069535,

Republic Of Singapore

Tel. +65 6227 6365 - Fax. +65 6225 6286

www.chemtradeasia.com



Other Protection: Provide eyewash, quick drench. It is good industrial hygiene practice to minimize eye/skin contact.

Hygienic Work Routines: Wash at the end of each working shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated.

Section 9 : Physical And Chemical Properties.

Appearance : Liquid.

Odour/Taste : Characteristic.

Physical Data Comments : Aromatic %vol. 17-20

Solubility Description : Insoluble in water

Specific Gravity (water=1) : 0.80 at 15° C

Viscosity : 0.95 x 10 (-6) m2/sec

Flash Point Method : CC (Closed cup)

Auto Ignition Temperature (° C) : 230 Flammability Limit (upper%) : N/D

Colour : Colourless

Boiling Point : 150 – 200

Flash Point (° C) : 42

Flammability Limit (lower %) : N/D

Section 10 : Stability And Reactivity

Stability : Avoid heat, sparks, and flames.

Conditions to Avoid : Avoid direct sunlight.

Materials to Avoid : Strong oxidising agents.

Hazardous Decomposition Products : Carbon monoxide (CO).

Oxides of : Carbon

Section 11 : Toxicological Information

Toxicological Information:

133 Cecil Street # 12-03 Keck Seng Tower, Singapore 069535,

Republic Of Singapore

Tel. +65 6227 6365 - Fax. +65 6225 6286

www.chemtradeasia.com



Toxicity following a single exposure to high Levels of White Spirit (oral, dermal, inhalation) is of a very low order. Prolonged contact or repeated contact may cause drying of the skin and possibly dermatitis. Prolonged inhalation of mists may cause lung inflammation.

Medical Considerations: Skin disorders and allergies.

Section 12 : Ecological Information

Environmental Hazards: Can be expected to biodegrade slowly.

Acute Fish Toxicity: Slightly toxic to aquatic organisms, but in most systems unlikely to perish for sufficient time to pose a significant hazard.

Section 13 : Disposal Considerations

Disposal Methods: Incinerate in suitable combustion chamber. Confirm disposal procedures with environmental engineer and Local regulations.

Section 14 : Transport Information

Label for Conveyance : Red Flammable Liquid 3 Triangle.

Road:

UN No : 1300 ADR Class No: 3

ADR Item No : 31 (c) ADR Class No: 3

Hazchem Code : 3[Y]

Proper Shipping Name : Turpentine Substitute

Rail:

Sea:

Sea Transport Class No : 3 IMDG Page No: 3375

Sea Pack GR : III

Marine Pollutant : DEAD FISH SYMBOL

Air:

Air Transport Class No : 3 Air Pack GR : 3

Section 15 : Regulatory Information

133 Cecil Street # 12-03 Keck Seng Tower, Singapore 069535,

Republic Of Singapore

Tel. +65 6227 6365 - Fax. +65 6225 6286

www.chemtradeasia.com



EEC (EINECS) No: 265-185-4

Labels For Supply: HARMFUL DANGEROUS FOR THE ENVIRONMENT

Risk Phrases: R-10 Flammable

R-65 Harmful: May Cause lung damage if swallowed.

R- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

Safety Phrases : S-2 Keep out of the reach of children.

S-24/25 Avoid contact with skin & eyes.

S-62 If swallowed, do not induce vomiting. Seek Medical advice.

S-61 Avoid release to the environment. Refer to special

instructions/Safety Data Sheets.

S-23 Do not breathe vapour or spray.

S-43 In case of fire use foam /dry powder /Co2 – NEVER USE WATER.

Guidance Notes : Environmental classification is recommended by the SIA with reference to the

CEFIC Hydrocarbon Solvents sector Group proposals based on 'The Aqueous

Environmental Classification of complex Petroleum Solvent Streams under The

EC Substances Directive (67/548/EEC).

Section 16 : Other Health And Safety Information

User Notes: For further Health & Safety information contact: Health & Safety Officer. This M.S.D.S has been issued in accordance with the chemicals (Hazard Information and Packaging for Supply) Amendment Regulations 1996. The HSE is permitting the use of R65. In place of R22 for hydrocarbon solvents classified harmful due to their Aspiration Hazard" ahead of the UK's formal Implementation of the 22nd ATP of the EU DSD."

If this product is re-distributed and re-formulated for sale, details of its hazards and recommended methods for safe handling must be passed to customers. Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a

133 Cecil Street # 12-03 Keck Seng Tower, Singapore 069535, Republic Of Singapore

Tel. +65 6227 6365 - **Fax**. +65 6225 6286

www.chemtradeasia.com



suitable and sufficient assessment of the risks created by a work activity using this product is undertaken before this product is used.

Note: The information contained in this Safety Data Sheet does not constitute the users own assessment of workplace risk as required by other Health & Safety Legislation (e.g. the Health and Safety at Work Act, 1974; the control of Substances Hazardous to Health Regulations, 1988). The data given here is based on current knowledge and experience. The purpose of this data sheet is to describe the products in terms of their safety requirements. The data does not signify any warranty with regard to the product's properties.

