

MATERIAL SAFETY DATA SHEET

METHYL ACETATE

1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MSDS Name : Methyl acetate
Synonyms : Acetic Acid Methyl Ester
Company Identification : Tradeasia International Pte Limited
Address : 133 Cecil Street # 12-03 Keck Seng Tower, Singapore
Tel : +65-6227 6365
Fax : +65-6225 6286
Email : contact@chemtradeasia.com

2 COMPOSITION AND INFORMATION ON INGREDIENTS

CAS#	Chemical Name	% by Weight
79-20-9	Methyl acetate	99.5

3 HAZARDS IDENTIFICATION

Potential Acute Health Effects:

Very hazardous in case of skin contact (permeator), of eye contact (irritant), of ingestion, of inhalation. Hazardous in case of skin contact (irritant). Inflammation of the eye is characterized by redness, watering, and itching.

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance is toxic to lungs. Repeated or prolonged exposure to the substance can produce target organs damage.

4 FIRST AID MEASURES

Eye Contact:

Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Do not use an eye ointment. Seek medical attention.

Skin Contact:

After contact with skin, wash immediately with plenty of water. Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. Cold water may be used. Cover the irritated skin with an emollient. If irritation persists, seek medical attention. Wash contaminated clothing before reusing.

Serious Skin Contact:

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek medical attention.

Inhalation:

Allow the victim to rest in a well ventilated area. Seek immediate medical attention.

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.

Ingestion:

Do not induce vomiting. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.

Serious Ingestion: Not available.

5 FIRE AND EXPLOSION DATA

Flammability of the Product	: Flammable.
Auto-Ignition Temperature	: 501.67°C (935°F)
Flash Points	:
CLOSED CUP: -10°C (14°F). OPEN CUP: -5.56°C (22°F) (Cleveland).	
Flammable Limits	: LOWER: 3.1% UPPER: 16%
Products of Combustion	: These products are carbon oxides (CO, CO ₂).
Fire Hazards in Presence of Various Substances	:

Highly flammable in presence of open flames and sparks, of heat, of oxidizing materials.

Fire Fighting Media and Instructions :

Flammable liquid, soluble or dispersed in water. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog.

Special Remarks on Fire Hazards :

May explode when heated. Vapor may travel considerable distance to source of ignition and flash back. When heated to decomposition it emits acrid smoke and fumes.

Special Remarks on Explosion Hazards : Not available.

Explosion Hazards in Presence of Various Substances :

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

6 ACCIDENTAL RELEASE MEASURES

Small Spill:

Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.

Large Spill:

Flammable liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

7 HANDLING AND STORAGE

Precautions:

Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapour/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, acids, alkalis, moisture.

Storage:

Flammable materials should be stored in a separate safety storage cabinet or room. Keep away from heat. Keep away from sources of ignition. Keep container tightly closed. Keep in a cool, well-

ventilated place. Ground all equipment containing material. A refrigerated room would be preferable for materials with a flash point lower than 37.8°C (100°F).

8 EXPOSURE CONTROLS/ PERSONAL PROTECTION

Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal Protection:

Splash goggles, Lab coat and Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles, Full suit, Vapor respirator, Boots and Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:

TWA: 200 CEIL: 250 (ppm) from ACGIH (TLV) TWA: 610 CEIL: 760 (mg/m³) from ACGIH Consult local authorities for acceptable exposure limits.

9 PHYSICAL AND CHEMICAL PROPERTIES

Physical state and appearance	: Liquid.
Odor	: Fragrance like.
Taste	: Not available.
Molecular Weight	: 74.08 g/mole
Color	: Colorless.
pH (1% soln/water)	: 7
Boiling Point	: 57°C (134.6°F)
Melting Point	: -98.05°C (-144.5°F)
Critical Temperature	: Not available.
Specific Gravity	: 0.92 (Water = 1)
Vapor Pressure	: 173 mm of Hg (@ 20°C)
Vapor Density	: 2.8 (Air = 1)
Volatility	: Not available.

Odor Threshold	: Not available.
Water/Oil Dist. Coeff.	: Not available.
Ionicity (in Water)	: Not available.
Dispersion Properties	: See solubility in water, methanol and diethyl ether.
Solubility	: Easily soluble in methanol, diethyl ether and Soluble in cold water, hot water.

10 STABILITY AND REACTIVITY DATA

Stability	: The product is stable.
Instability Temperature	: Not available.
Conditions of Instability	: Not available.
Incompatibility with various substances	: Reactive with oxidizing agents, acids, alkalis, moisture.
Corrosivity	: Non-corrosive in presence of glass.
Special Remarks on Reactivity	: Not available.
Special Remarks on Corrosivity	: Not available.
Polymerization	: No.

11 TOXICOLOGICAL INFORMATION

Routes of Entry: Dermal contact. Eye contact. Inhalation. Ingestion.

Toxicity to Animals:

Acute oral toxicity (LD50): 5001 mg/kg [. Rat]. Acute dermal toxicity (LD50): 5001 mg/kg [Rabbit].

Chronic Effects on Humans:

The substance is toxic to lungs.

Other Toxic Effects on Humans:

Very hazardous in case of skin contact (permeator), of ingestion, of inhalation. Hazardous in case of skin contact (irritant).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans:

Exposure can cause nausea, headache and vomiting. Material is irritating to mucous membranes and upper respiratory tract.

12 ECOLOGICAL INFORMATION

Ecotoxicity : Not available.

BOD5 and COD : Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation:

The products of degradation are more toxic.

Special Remarks on the Products of Biodegradation : Not available.

13 DISPOSAL CONSIDERATIONS

Waste Disposal: Not available.

14 TRANSPORT INFORMATION

DOT Classification : Class 3: Flammable liquid.

Identification : Methyl acetate : UN1231 PG: II

Special Provisions for Transport : Not available.

15 OTHER REGULATORY INFORMATION

Federal and State Regulations:

Pennsylvania RTK: Methyl acetate Massachusetts RTK: Methyl acetate TSCA 8(b) inventory: Methyl acetate

Other Regulations:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications:

WHMIS (Canada):

CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2A: Material causing other toxic effects (VERY TOXIC).

DSCL (EEC):

R11- Highly flammable. R38- Irritating to skin. R41- Risk of serious damage to eyes.

HMIS (U.S.A.):

Health Hazard	: 1
Fire Hazard	: 3
Reactivity	: 2
Personal Protection	: h

National Fire Protection Association (U.S.A.):

Health	: 1
Flammability	: 3
Reactivity	: 0

Protective Equipment:

Gloves, Lab coat and Dust respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash goggles.

16 OTHER INFORMATION

References: Not available.

Other Special Considerations: Not available.

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall Tradeasia International Pte. Ltd. Be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Tradeasia International Pte. Ltd. has been advised of the possibility of such damages.